## (19) World Intellectual Property Organization

International Bureau



## 

(43) International Publication Date 18 August 2005 (18.08.2005)

 $\mathbf{PCT}$ 

## (10) International Publication Number WO 2005/075272 A1

- (51) International Patent Classification7: B61G 5/02, 9/04
- (21) International Application Number:

PCT/SE2005/000071

- (22) International Filing Date: 25 January 2005 (25.01.2005)
- (25) Filing Language:

Swedish

(26) Publication Language:

English

(30) Priority Data: 0400215-0

4 February 2004 (04.02.2004)

- (71) Applicant (for all designated States except US): DELL-NER COUPLERS AB [SE/SE]; Vikavägen 144, S-791 95 Falun (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): HOGBRING, Magnus [SE/SE]; Kung Magnigatan 23, S-791 62 Falun (SE).
- (74) Agent: DR. LUDWIG BRANN PATENTBYRÅ AB; P.O. Box 17192, S-104 62 Stockholm (SE).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TOWING ARRANGEMENT AND DEFORMATION TUBE IN A RAILWAY VEHICLE COUPLING



(57) Abstract: The invention relates to a rowing arrangement being intended for train couplers and of the type that a migrises a bar (8), which at a rear end has an atially projecting with (10), which projects through a through hotel (40) in a plate (11), which or, hotel sides is surrounded by snoor-absorbing spring that hers (1), which always aim to hold the pin in a starting position in relation to the plate, and against the action of which the pin to go not with the bar are axial pincovable. According to the invention the plate () I is included in a mandrel det segaipped with a case of which mandrel is inserted into a deformation tube (17), more practices into a wide, from table section 12), which via a wais 12) to asforms into a thinner, rear tube section (21), which is do terrante by the mandrel () 6). In a particular aspect the invention also relates to a deformation tube as such.